

Таблица по AWG (многожильный провод)

Многожильный провод				
AWG	Диаметр, мм	Площадь сечения, мм²	Погонное сопротивление, Ом/км	Погонный вес, кг/км
4	19x7x0.455	6.6	0.85	197.9
6	19x7x0.361	5.3	1.35	124.9
8	19x7x0.287	4.2	2.15	79.0
10	37x0.404	2.8	3.94	44.4
10	105x0.254	3.2	3.90	49.3
12	19x0.450	2.25	6.10	28.1
12	63x0.254	2.35	5.92	29.0
14	19x0.361	1.8	9.61	17.7
14	41x0.254	1.8	9.10	18.9
16	19x0.287	1.43	15.2	11.2
16	25x0.254	1.53	14.9	11.5
18	7x0.404	1.22	22.0	8.2
18	16x0.254	1.27	25.8	7.4
18	19x0.254	1.27	19.7	8.8
20	7x0.320	0.96	33.2	5.2
20	10x0.254	1.02	37.3	4.6
20	19x0.203	1.01	31.0	5.6
22	7x0.254	0.76	53.3	3.3
22	19x0.160	0.80	49.5	3.5
24	7x0.203	0.61	83.4	2.1
24	19x0.127	0.63	78.5	2.2
26	7x0.160	0.48	134.1	1.28
26	19x0.102	0.50	121.6	1.42
28	7x0.127	0.381	212.9	0.807
28	19x0.079	0.390	208.0	0.821
30	7x0.102	0.306	330.1	0.521